





Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage $\Delta$ [V]	Base voltage Y [V]	Protection	Ins. Cl.	 <p>Teknomotor S.r.l. Via Argenega 31, I-32038 Quero Vas (BL) www.teknomotor.com</p>
3.3	S1	18000	300	220	380	IP54	F	
Min speed [rpm]		Max speed [rpm]	Max freq. [Hz]	Absorb. $\Delta$ [A]	Absorb. Y [A]	Part number on nameplate		
6000		24000	400	13.7	7.9	COM51600217		
Balancing: G2.5 - ISO 1940 @ maximum motor speed		Balancing type		tool type full key	tool type half key	Peso / weight		
						12.53 kg		
Tolleranze non quotate / unlisted tollerances: $\pm 0.5\text{mm}$ Smussi non quotati / unlisted chamfers: $\pm 0.5\text{mm}$				$\nabla = 0.8 \nabla$	$\nabla = 3.2 \nabla$	$\nabla = 12.5 \nabla$	$\sim = \nabla$	Title
								5160-A-DB-P-ER32-HY-RH
rev. n°	description			date	signature	Customer		
00	Emissione			18/05/2012	D. Bottarel	Catalogo		
drawing - date						Drawing code		Drawing n°
D. Bottarel - 18/05/2012		approved - date		checked - date		COM51600217		1866
S. Perli - 18/05/2012		S. Perli - 18/05/2012		sostituisce il		foglio / sheet	scala	
				sostituito dal		1 / 1	n.d.	