



USE DRIED AIR:
 ACCORDIND TO DIRECTIVE ISO 8573-1
 CLEANLNESS CLASS 2/4/3
 SOLID PARTICLES: 1 mincron/1PPM
 HUMIDITY: DEW POINT 3°C
 OIL: 1mg/m³
 USE 5 micron FILTER +
 0,1 micron min OIL SEPARATOR.

Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Base voltage Y [V]	Protection	Ins. Cl.
3.3	S1	18000	300	220	380	IP64	F
Min speed [rpm]		Max speed [rpm]	Max freq. [Hz]	Absorb. Δ [A]	Absorb. Y [A]	Part number on nameplate	
6000		24000	400	13.7	7.9	COM51600342	
Balancing: G2.5 - ISO 1940 @ maximum motor speed		Balancing type		tool type full key	tool type half key	Peso / weight	
						12.56 kg	
Tolleranze non quotate / unlisted tollerances: ±0.5mm Smussi non quotati / unlisted chamfers: ±0.5mm				$\nabla = 0.8 \nabla$	$\nabla = 3.2 \nabla$	$\nabla = 12.5 \nabla$	$\sim = \nabla$
rev. n°	description			date	signature	Customer	
00	Emissione			10/07/2014	D. Bottarel	Catalogo	
drawn - date						approved - date	checked - date
D. Bottarel - 10/07/2014						S. Perli - 10/07/2014	S. Perli - 10/07/2014
sostituisce il						sostituito dal	
foglio / sheet						scala	
1 / 1						n.d.	A4



Teknomotor S.r.l.
 Via Argenegea 31, I-32038 Quero Vas (BL)
 www.teknomotor.com

Title
5160-A-DB-P-ER32-PR-HY-RH

Drawing code
COM51600342

Drawing n°
3288